Power supply
Alimentation
Fuente de alimentación
12VDC – 5 A
FE-302

Conector ref. C-4413

Technical characteristics

Name : 12V 5A power adapter	Start time : ≤ 3s (240VAC input, io=100%)
Input Voltage : AC 100-240V	Guard time : ≥ 20ms (240VAC input, io=100%)
Output Voltage : DC 12V 5A	Overload protection : 130% - 150% rated power, automatic recovery
Frequency range : 50/60Hz	Over-voltage protection : 115% - 135% , automatic recovery
Conversion efficiency : ≥ 80%	Working temperature : -10°C ~+ 70°C
Leakage Current : < 1mA / 240VAC	Working humidity : 20% - 90%RH
Ripple & Noise : (mVp-p): < 120	Storage temperature : -40°C ~ +85°C

Cerbek power supply, which is supplied with a special terminal connector, in case you want to use it in any of our assemblies.
It is also often used for LED strips, and for laptop power, LCD, TFT.

CE-TUV-GS certificates.

Alimentation Cerbek, qui est fournie avec un connecteur de borne spécial, au cas où vous souhaiteriez l'utiliser dans l'un de nos assemblages.
Il est également souvent utilisé pour les bandes LED et pour l'alimentation des ordinateurs portables, LCD, TFT.

Certificats CE-TUV-GS.

Fuente de alimentación de Cerbek, que se suministra con conector especial para bornes, por si quieres usarla en cualquiera de nuestros montajes.
Suele usarse también para tiras de led, y para alimentación de portátiles, LCD, TFT ..

Certificados CE-TUV-GS .

Cebek ® is a registered trademark of the Fadisel group

www.cebek.com - sat@fadisel.com